



Acoustic Panels

Transform your space.

Wallworks eKōR acoustical panels provide outstanding sound absorption and a unique appearance with minimal installation effort.







Description

eKōR PET Panels are sound absorbing panels developed with environmental friendliness in mind. eKōR offers additional benefits compared to traditional acoustic board material that allows it to be installed as is with no covering. These include higher tack-abiliy and resiliency, as well as being free of allergens, toxins, irritants, binding agents and formaldehyde.

Core Material

100% PET (60% PET-recycled fiber and 40% PET-virgin fiber) and are 100% recyclable.

Fire Performance

ASTM E84 and CAN/ULC S102

Thickness

Available in 9mm, 12mm, 25mm.

Panel Sizes

Standard 1200mm x 2400mm Custom shapes, sizes and perforations available

Mounting Options

Concealed Nail, Decor Screw, Impalit Strip or Adhesive direct to wall

Applications

Theaters & home theaters
Gymnasiums & multipurpose rooms
Commercial & office buildings
Studios & production houses
Restaurants & night clubs
Government & municipal buildings
Schools & universities
Industrial & manufacturing facilities

Acoustical Performance

Thickness	Mount	125HZ	250HZ	500HZ	1KHz	2KHz	4KHz	NRC
1/2"	Type A	0.07	0.09	0.16	0.47	0.91	0.75	0.40
1/2"	Type E200	0.69	0.92	0.96	0.76	0.79	0.74	0.85

Type A - Signifies panels that are mounted/installed directly onto a wall or ceiling. Type E200 - Signifies panels that are installed with 200mm air space behind.

Contact our sales team for detailed options and pricing:

Toll Free: 877.829.2550 sales@wallworks.com Fax: 855.896.8893 www.wallworks.com

Find us on:









Colour Selection (9 mm)



Toll Free: 877.829.2550 sales@wallworks.com Fax: 855.896.8893 www.wallworks.com











Colour Selection (9 mm)



Toll Free: 877.829.2550 sales@wallworks.com Fax: 855.896.8893 www.wallworks.com





