


**Transform your space.**

Wallworks Perforated Metal acoustical panels provide outstanding sound absorption and a unique appearance with minimal installation effort.



**Description**

Wallworks Perforated Metal acoustic Panels are the ideal choice for usage in applications requiring high performance, abuse-resistant acoustic panels that favour a clean finish.

**Assembly Materials**

Standard 22ga perforated sheet steel facing. Standard perforation size is 2.4 mm (3/32") circular holes on 4.8 mm (3/16") staggered centers, providing 23% open area. Custom gauges and perforation patterns available upon request.

Powder-coated finish on face of steel, available in all standard RAL colors. Other custom finishes may be available upon request.

**Thickness**

Standard 2" thick #2.5 / cu.ft. fibreglass acoustic underlay (may also substitute with mineral wool insulation), wrapped in black polyethelene. Other thicknesses and densities available.

**Fire Performance**

ASTM E84 and CAN/ULC S102

**Mounting Options**

Custom framing and finishing system to suit site conditions and panel sizes. Mechanical fastener mounting system is standard.

**Panel Sizes**

Custom shapes, sizes and perforations available

**Acoustical Performance**

Frequency, Hz	125	250	500	1000	2000	4000	NRC
Absorption Coefficient	0.22	0.77	1.12	1.00	0.78	0.57	0.90

Contact our sales team for detailed options and pricing:

Toll Free: 877.829.2550

sales@wallworks.com

Fax: 855.896.8893

www.wallworks.com

Find us on:

